

**AMENDMENTS TO THE CLAIMS:**

1. (Currently Amended) An image pickup apparatus comprising:

lens group drive means for driving a lens group to adjust a focal point of said lens group;  
image pickup means for generating a plurality of screens having different exposure  
conditions, each of the generated screens having a different focal voltage associated with a  
subject, wherein the plurality of screens are adjacent temporally and in different exposure  
conditions, and said plurality of screens are synthesized to form a synthesized image;  
means for detecting the focal voltage voltages from of each of said plurality of screens  
and storing said detected focal voltagesvoltage of each respective screen, said focal voltages  
voltage containing high-frequency components included in each of said plurality of screens; and  
focal voltage selecting means for selectively outputting the focal voltage of one of the  
plurality of screens one of said stored focal voltages that is most suited to obtain a desired focus  
intended by the userbased on the basis of a predetermined selection criterion;  
wherein automatic focusing is carried out in accordance withaccording to said focal  
voltage outputted from said focal voltage selecting means.

2. (Cancelled)

3. (Currently Amended) An image pickup apparatus according to Claim 1, wherein  
[[in]] during said automatic focusing, said focal voltage selecting means keeps on continuously  
provides a outputtingsaid focal voltage that is outputted at the time that of starting to drive said  
lens group is initially driven, for [[in]] a period from starting of drive of said lens group are  
initially driven until a desired focus is reached, to conclusion of reaching focus to thereby stop  
moving said lens group.

4. (Original) An image pickup apparatus according to Claim 1, wherein said focal voltage selecting means selectively outputs a focal voltage for focusing in accordance with magnitudes of said stored focal voltages inputted to said focal voltage selecting means.

5. (Previously presented) An image pickup apparatus according to Claim 1, wherein said focal voltage selecting means selectively outputs a focal voltage for focusing on the basis of a comparison among luminance level frequency distributions belonging to said screens respectively associated with said stored focal voltages inputted to said focal voltage selecting means.

6. (Previously presented) An image pickup apparatus according to Claim 1, wherein said focal voltage selecting means varies said selection criterion in accordance with magnitudes of said stored focal voltages inputted to said focal voltage selecting means and luminance level frequency distributions belonging to said screens respectively associated with said stored focal voltages.

Claims 7-16 (Cancelled)

17. (New) The image pickup apparatus according to claim 1, wherein: the focal voltage selecting means is configured to perform a step to compare the focal voltage of each of the plurality of screens obtained under different exposure conditions, and update the focal voltage that is most suited to obtain the desired focus based on a result of the comparing step; and

the lens group drive means adjusts the focal point of said lens group based on the updated focal voltage that is most suited to obtain the desired focus.